

APPLICATION

The Datacomm Category 6 unshielded Keystone Jack is manufactured using quality materials and engineering standards to exceed the latest ANSI/TIA/EIA 568B. 2-10 performance at 250Mhz. The Keystone Jack outlet is suitable for mounting in a range of faceplates and snap-in patch panels.



FEATURES & BENEFITS

1. **Reliable Design:** Automatic production ensures stability.
2. **Toolless Install:** No punch-down tool required.
3. **Standard Compliance:** Meets Cat6 performance standards.
4. **Durable:** Built for long-lasting use.
5. **Color-Coded:** Simplifies wiring installation.
6. **Compact:** Fits in tight spaces.
7. **Versatile:** Works with solid and stranded cables.

SPECIFICATION

TECHNICAL SPECIFICATION		
Cables Supported	SOILD AND STRANDED	
	22AWG/23AWG/24AWG	
Electrical	Contact Resistance	20m OHM
	Insulation Resistance	<= 250M OHM @100 V DC
	Withstand Voltage	DC1000V AC700V RMS 60HZ, IMIN
	Cat6 Permanent Link	CONFORM TO ANSI/TIA/EIA 568B. 2-10
Environmental	Storage	-40°/ +70°
	Operation	-10°/ +60°
Mechanical	Plastic Material	New Polycarbonate
	Gold Pins	PHOSPHOR BRONZE, GOLD PLATING 50U”
	Terminal Pins	PHOSPHOR BRONZE, TIN PLATING
	IDC Terminal Life	250 TIMES MIN
	RJ45 Contact Life	750 TIMES MIN

Ordering Information

Part Number	Product Description
&1873.6	\$\$200&\$873.WRQFRROO&SI