

# DCN-NVR-8CH-2HDD-ECO-POE

DCN 8ch 2HDD NVR with 8ports POE, Eco series



## Key Features


- Up to 8-ch IP cameras access
- Up to 80 Mbps incoming/outgoing bandwidth
- Up to 1-ch @ 12MP/4-ch @ 4MP/8-ch @ 1080P decoding capacity
- Support mask detection, face recognition and multi-objective recognition
- Support VCA alarm linkage
- Up to 4-ch perimeter protection
- Plug & Play with 8 PoE interface
- Support 1 HDMI and 1 VGA interface

## Specification

Video Input	
IP Camera Input	8 Channel
Incoming Bandwidth	80 Mbps
Outgoing Bandwidth	80 Mbps
Video Output	
HDMI Output	3840 × 2160, 1920 × 1080, 1280 × 1024, 1024 × 768
VGA Output	1920 × 1080, 1280 × 1024, 1024 × 768
Different Source Output	Support
Decoding Capacity	1ch 12MP, 4ch 4MP, 8ch 1080P Enable Local Intelligence: 1ch 8MP, 4ch 1080P, 8ch D1
Dual Stream	Support
Multi-screen Display	1/4/9
AI Recognition	
Face Comparison	Real-time captured and display faces comparison results (registrant (name and ID), stranger, channel, similarity)
Multi-objective	Real-time captured and display vehicle, human body, non-motor vehicle, license plates image, and faces comparison results (registrant, stranger, channel, similarity)
Smart Search	Time, Properties, Pictures, License plate
Trigger Events	Buzzer, Alarm push, Alarm prompt, Email, Alarm Out, Compare the result simultaneously, etc.
Recoding	
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.
Recording Mode	Manual, Schedule (Regular, Continuous), Event
Trigger Events	Motion Detection, Video Loss, Alarm in, IVS
Playback and Backup	
Sync Playback	8/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Backup Mode	USB Device, Network
Alarm	
General Alarm	Motion Detection, Video Loss, Alarm in, Alarm out
Intelligent Analysis (By Camera)	Smoking Detection, Smoke and Fire Detection, Fire Spot Detection, Intrusion, Single Line Crossing, Double Line Crossing, Loitering, Wrong-way, Illegal Parking, People Counting, Smart motion detection, Enter Area, Leave Area, etc.
Abnormal Alarm	Disk Alarm, IP Address Conflict, Network Disconnect
Intelligent Analysis (By NVR)	4-ch intrusion detection, support the accurate detection of human and vehicle

Event Action	Buzzer, Push message to APP, Pop up message to monitor, Full screen, Email, FTP, PTZ, Alarm output, Recording
<b>Network</b>	
Network Protocol	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, FTP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE
Remote Users	8 users
P2P	P2P, Web NAT
Interoperability	ONVIF, SDK, CGI
<b>Storage</b>	
ANR	Support
Disk Group	Support
<b>Interface</b>	
HDD Interface	2 SATA interfaces, up to 12TB capacity for each disk
Network Interface	1 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
PoE Interface	8 ports, 10/100Mbps, 802.3af/at, max 128W
HDMI	1
VGA	1
Audio In/Out	1/1
Alarm In/Out	8/1
USB Interface	Front panel: 2 × USB 2.0, Rear panel: 1 × USB 2.0
Reset Button	On-board reset button
<b>General</b>	
Power Supply	100 to 240VAC
Power Consumption	< 15 W (without HDD)
Operating Conditions	-10 °C to 50 °C (14 °F to 122 °F)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	372 × 311.2 × 46.4 mm (16.65 × 12.33 × 1.83 inch)
Net Weight	2.1 kg (4.63 lb) without HDD

# Dimensions (mm)



# Rear Panel

