

DCN-NVR-8CH-1HDD-ECO-POE

DCN 8ch 1HDD NVR with 8ports POE, Eco series



Key Features


- Up to 8-ch IP cameras access
- Up to 80 Mbps incoming/outgoing bandwidth
- Up to 1-ch @ 12MP/4-ch @ 4MP/8-ch @ 1080P decoding capacity
- Support mask detection, face recognition and multi-objective recognition
- Support VCA alarm linkage
- Up to 4-ch perimeter protection
- Plug & Play with 8 PoE interface
- Support 1 HDMI and 1 VGA interface

Specification

| Video Input | |
|----------------------------------|---|
| IP Camera Input | 8 Channel |
| Incoming Bandwidth | 80 Mbps |
| Outgoing Bandwidth | 80 Mbps |
| Video Output | |
| HDMI Output | 3840 × 2160, 1920 × 1080, 1280 × 1024, 1024 × 768 |
| VGA Output | 1920 × 1080, 1280 × 1024, 1024 × 768 |
| Different Source Output | Support |
| Decoding Capacity | 1ch 12MP, 4ch 4MP, 8ch 1080P Enable Local Intelligence: 1ch 8MP, 4ch 1080P, 8ch D1 |
| Dual Stream | Support |
| Multi-screen Display | 1/4/9 |
| AI Recognition | |
| Face Comparison | Real-time captured and display faces comparison results (registrant (name and ID), stranger, channel, similarity) |
| Multi-objective | Real-time captured and display vehicle, human body, non-motor vehicle, license plates image, and faces comparison results (registrant, stranger, channel, similarity) |
| Smart Search | Time, Properties, Pictures, License plate |
| Trigger Events | Buzzer, Alarm push, Alarm prompt, Email, Alarm Out, Compare the result simultaneously, etc. |
| Recoding | |
| Resolution | 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc. |
| Recording Mode | Manual, Schedule (Regular, Continuous), Event |
| Trigger Events | Motion Detection, Video Loss, Alarm in, IVS |
| Playback and Backup | |
| Sync Playback | 8/4/1 |
| Search Mode | Time /Date, Alarm, Picture grid, Event |
| Backup Mode | USB Device, Network |
| Alarm | |
| General Alarm | Motion Detection, Video Loss, Alarm in, Alarm out |
| Intelligent Analysis (By Camera) | Smoking Detection, Smoke and Fire Detection, Fire Spot Detection, Intrusion, Single Line Crossing, Double Line Crossing, Loitering, Wrong-way, Illegal Parking, People Counting, Smart motion detection, Enter Area, Leave Area, etc. |
| Abnormal Alarm | Disk Alarm, IP Address Conflict, Network Disconnect |
| Intelligent Analysis (By NVR) | 4-ch intrusion detection, support the accurate detection of human and vehicle |

| | |
|----------------------|---|
| Event Action | Buzzer, Push message to APP, Pop up message to monitor, Full screen, Email, FTP, PTZ, Alarm output, Recording |
| Network | |
| Network Protocol | HTTP, HTTPS, TCP/IP, IPv4, IPv6, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, FTP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE |
| Remote Users | 8 users |
| P2P | P2P, Web NAT |
| Interoperability | ONVIF, SDK, CGI |
| Storage | |
| ANR | Support |
| Interface | |
| HDD Interface | 1 SATA interfaces, up to 12TB capacity for each disk |
| Network Interface | 1 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port |
| PoE Interface | 8 ports, 10/100Mbps, 802.3af, max 72W |
| HDMI | 1 |
| VGA | 1 |
| Audio In/Out | 1/1 |
| Alarm In/Out | 8/1 |
| USB Interface | Front panel: 2 × USB 2.0, Rear panel: 1 × USB 2.0 |
| Reset Button | On-board reset button |
| General | |
| Power Supply | 48VDC/2A |
| Power Consumption | < 15 W (without HDD) |
| Operating Conditions | -10 °C to 50 °C (14 °F to 122 °F) |
| Storage Conditions | Less than 90% RH |
| Certifications | CE/FCC |
| Dimensions | 255 × 235.0 × 45.3 mm (10.04 × 9.25 × 1.78 inch) |
| Net Weight | 1 kg (2.2 lb) without HDD |

Dimensions (mm)



Rear Panel

